



# COUNTERTOP FRYERS



LD56 fryer

## KEY FEATURES

- Two models availability
  - choose to suit your level of business
- One-piece, stainless steel plunged hob and pan
  - easy to clean
- Easy to remove element box(es)
  - stand up to rigorous use
- Supplied with 13A plug(s)
  - plug and use straight out of the packaging

## MODELS and ACCESSORIES

LD50 single pan fryer (7 litre)

LD56 twin pan fryer (2 x 7 litre)

- No accessories

## MODEL DIMENSIONS (in mm)

LD50 : 300mm (w) x 630mm (d) x 315mm (h)

LD56 : 600mm (w) x 630mm (d) x 315mm (h)

## SPECIFICATION DETAILS

	LD50	LD56
Rating (kW)	2.75	2 x 2.75
Supply voltage	230V~	230V~
Current split (amps)	L1: 13	L1: 2 x 13
Chip output (kg per hour)	8.5	17
No. of baskets	1	2
Weight (kg)	12.5	25
Packed weight (kg)	14	26

## INSTALLATION NOTES

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health.

Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. A clearance of 150mm should be observed between appliance and any combustible wall.

