

E3800DXBrattPan

Key features

- Stainless steel pan with duplex steel base
 Delivers even heating across the base of the pan
- Versatile cooking performance
 - Able to carry out six different cooking methods
- Manual tilt via front located handle
 Safe, smooth pan tilting
- Incremental opening lid
 See what's cooking without unnecessary heat loss
- Precise temperature control from 100 300°C
 - Responsive and accurate controls
- Automatic power cut-off when pan is tilted
 Additional safety feature for added peace of mind
- Integrated water faucet
 - Easy to add water to pan as and when required
- Laser-etched control icons
 - Permanent, indelible markings

Accessories

- Steaming tray
- 1/1 GN compatible cradle
- Factory fitted, adjustable castors
- Fixed installation kit


Similar Models

- E9781 100 litre bratt pan
- G3800DX Gas bratt pan
- G9781100 litre electric bratt pan



DOMINATORPLUS

E3800DX Bratt Pan




Measurements in mm

92 water inlet



102 elec. inlet



Unit is the same now neight on reet and castors

Specification details

Electrical rating (kW)	7.6
Electrical supply voltage	400V 3N~
Electrical current split (A)	L1: 11.2 L2: 11.2 L3: 11.2
Pan dimensions (w x d x h - mm)	720 x 430 x 200
Water capacity (litres)	60
Water connection (BSP)	1/2"
Weight (kg)	118
Packed weight (kg)	131
Packed dimensions (w x d x h - mm)	1000 × 1000 × 1100
GTIN numbers	On feet On castors

Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.

