



PRO-LITE

LD48 Twin Pan Freestanding Fryer

Key features

- Integrated oil drainage system
 - Oil drainage bucket provided below pan
- Lift out control boxes at rear of fryer
 - Simple to remove for cleaning
- Supplied with lid as standard
 - Protects cooking oil when not in use
- Stainless steel finish
 - Easy to clean and keep clean

Accessories

- Additional basket

Similar Models

- LD46 single pan fryer
- LD56 countertop twin pan fryer
- LD50 countertop single pan fryer

Specification *details*

Electrical rating (kW)	2 x 6
Electrical supply voltage	400V 2N~
Electrical current split (A)	2 x (L1: 13 L2: 13)
Oil capacity (litres)	2 x 8
Chip output (kg/hour)	2 x 20
Weight (kg)	50
Packed weight (kg)	53
Dimensions (w x d x h - mm)	600 x 630 x 965
Packed dimensions (w x d x h - mm)	650 x 700 x 1100
GTIN number	5056466905804

Installation notes

Adequate ventilation must be provided to supply sufficient fresh air for combustion and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit, draught free position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.