



Product Code: RBCT20-60 Remote 17-119

Roll-In Blast Chiller Cabinet (Remote)



Features & Benefits

- Specific model to accept the Rational 201 trolley with a chilling capacity of 60kgs
- Chilling capacity 90°C to 3°C in less than 90 minutes within specifications. Entry temperature up to 90°C for chilling
- For ventilation and service access ensure that 400mm minimum clearance is allowed above the unit

Base Fittings

Remote Refrigeration System Option

Electrical & Service Data

Connect Load 750

400/50/3 Standard

Fuse Required (A) 16

Doors

Solid Standard

Specification

Blast Chiller Standard

Width (mm) 980

Depth (mm) 865

Height (mm) 2190

Chilling Capacity (Kgs) 60 kg

Gross Volume (Ltr) 60 kg

Refrigeration

On Application Standard

Integral Refrigeration System Standard

Drain Rqd 1 1/2 BSP

Finish

304 s/s Standard

Footnotes

- Requires connection to external drain. 1x 1/2" BSP Drain outlet
- Chilling Capacity - 60 KG. Chilling capacity 90 degrees C to 3 degrees C in less than 90 minutes within specifications. Entry temperature of up to 90 degrees C for chilling.
- Dimensions: For ventilation and service access ensure that 400mm minimum clearance is allowed above the RBC 20-60
- Maximum Ambient 43 degrees C



Energy



Quality



Value



Design



Hygiene



After Care

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU

Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.