



VENTILATED UPRIGHT GASTRONORM REFRIGERATION

Available in a single or double door configuration, the KXR/KXF units feature a 201 stainless steel exterior and interior. Rounded corners allow the units to be easily cleaned and maintained only helped by the ability to easily move them around thanks to the heavy duty castors that are fitted as standard on all configurations.

Self-closing doors with dwell position, 3 adjustable shelves per door, 60mm thick insulation, led lighting and more all contribute to this amazing value products success.

MODEL	DOORS	SHELVES	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ ANNUM	POWER	WEIGHT (kg)
KXR600	1	3	600L	R290	-2°C ~ +8°C	H2000 x W680 x D840	D	195W	815	☒	125
KXF600	1	3	600L	R290	-18°C ~ -22°C	H2000 x W680 x D840	E	450W	2826	☒	132
KXR1200	2	6	1200L	R290	-2°C ~ +8°C	H2000 x W1340 x D840	D	380W	1382	☒	213
KXF1200	2	6	1200L	R290	-18°C ~ -22°C	H2000 x W1340 x D840	E	700W	4317	☒	221

OPTIONAL EXTRAS	DESCRIPTION
K8-GUIDE01	Guides for Shelf (pair)
K8-SHELF02	2/1 GN Shelf GN



SCAN FOR MORE INFO

