

LBC2NU



## REFRIGERATED COUNTERS WITH FLAT WORKSURFACE

With the same versatility of its upstand equipped sibling the HBC/LBC-NU range features heavy duty castors, replaceable door gaskets, self closing doors and more!

Featuring even air distribution via a ducted system, which allows ventilated cooling. Temperature can be monitored and controlled using a conveniently positioned dixell controller and ensure what ever you need to store away in these units will stay at its very best for as long as possible.

MODEL	DOORS	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ANNUM	POWER	WEIGHT (kg)
HBC2NU	2	282L	R290	+2°C ~ +8°C	H850 x W1360 x D700	C	215W	822	☼☼☼	128
HBC3NU	3	417L	R290	+2°C ~ +8°C	H850 x W1795 x D700	C	230W	1162	☼☼☼	154
HBC4NU	4	553L	R290	+2°C ~ +8°C	H850 x W2230 x D700	D	345W	1741	☼☼☼	185
LBC2NU	2	282L	R290	-18°C ~ -22°C	H850 x W1360 x D700	E	520W	2851	☼☼☼	133
LBC3NU	3	417L	R290	-18°C ~ -22°C	H850 x W1795 x D700	E	560W	3357	☼☼☼	179
LBC4NU	4	553L	R290	-18°C ~ -22°C	H850 x W2230 x D700	E	650W	3951	☼☼☼	196

OPTIONAL EXTRAS	DESCRIPTION
X1-DRAWERPACK2	HBC LBC XX RANGE 2 DRAWER CONVERSION
X1-DRAWERPACK3	HBC LBC XX RANGE 3 DRAWER CONVERSION
X1-SHELF02	Shelf
X1-GUIDE02	Guide (pair) for HBC and LBC

SCAN FOR MORE INFO

